

# GMT-300 BLACKOUT



GEMTECH® ALL RIGHTS RESERVED. For more information visit [www.gem-tech.com](http://www.gem-tech.com) for accessories, adapters, and ammunition. Manufactured by: GEMTECH, PO Box 140618, Boise, ID 83714. Phone: (208) 939-7222. Sales@gemtech.com

## WARRANTY AND DISCLAIMER:

READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS.

**LIMITED WARRANTY:** Gemini Technologies, Inc., DBA Gemtech, warrants to the initial retail purchaser that Gemtech products will be free of defects in workmanship or material and that the product meets manufacturing specifications at the time of manufacture. This warranty is limited to the repair or replacement of the product. This express limited warranty is exclusive and no other express or implied warranty is otherwise provided. GEMTECH MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. Product technical specifications and/or designs may be changed without notice. This warranty does not cover negligence, misuse, careless or improper handling and/or operation, abuse, unauthorized adjustments or modifications, improper mounting/installation, ordinary wear and tear, the failure to follow manufacturer instructions and/or the use of inappropriate or defective ammunition.

GEMTECH SHALL HAVE NO LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES AND UNDER NO CIRCUMSTANCES WILL GEMTECH BE LIABLE FOR PERSONAL INJURY, PROPERTY DAMAGE OR ECONOMIC LOSS.

This warranty and disclaimer is subject to all applicable laws some of which may limit these terms.

## WARRANTY REPAIRS: RETURN OF DAMAGED SUPPRESSORS:

If a suppressor is damaged due to a manufacturing defect once it has been fired, it may be returned to Gemtech for repair or replacement. Determination to repair or replace is made solely at our discretion and only after we have had the opportunity to examine and determine that the cause of damage is due to manufacturer defect. It is the responsibility of the customer to cover shipping costs and insurance to return the suppressor to Gemtech for inspection or repair. Gemtech will pay any reasonable shipping and insurance costs to return the unit to you. To ensure proper legal procedures for any repair returns, fill out and provide a copy of the **General Service Form** with any packages sent to us. (Visit: [gem-tech.com](http://gem-tech.com), navigate to CUSTOMER SUPPORT/RETURN & REPAIR POLICIES to download the **General Service Form.pdf** or call 208.939.7222).

BATFE no longer requires transfer on a Form 5 to the manufacturer for repair. BATFE does require a letter accompanying the suppressor detailing the repairs or modifications required. BATFE requires proof of ownership satisfied by a photocopy of the front of the owner's form 3,4, or 5.

NOTE: BATFE prohibits transferring the serial number to a new outer tube in the case of damage to the tube. Tube damage rendering the suppressor unsafe to use will require a new suppressor.



## BEFORE USING THIS SUPPRESSOR:

BE CERTAIN YOU HAVE READ AND UNDERSTAND THIS MANUAL. FAILURE TO FOLLOW INSTRUCTIONS IN THIS MANUAL CAN RESULT IN THE POTENTIAL FOR SERIOUS INJURY AND PROPERTY DAMAGE. USE EXTREME CARE AND CAUTION WHEN HANDLING ANY FIREARM AND SUPPRESSOR.

## AMMUNITION:

We encourage the use of Gemtech 300 BLK ammunition. (Visit: [gem-tech.com](http://gem-tech.com) for more information)



ONLY USE .300 BLACKOUT AMMUNITION MEETING SAAMI SPECIFICATIONS WITH THIS GEMTECH SUPPRESSOR.

## SAFETY WARNINGS:

Make sure suppressor is TIGHT to the shoulder of the barrel for proper alignment. Silencers are potentially dangerous. Safe and proper use is the responsibility of the product user. Gemtech is not responsible for improper use of this product.

## SPECIFICATIONS:

- SOUND REDUCTION: 36-39 dB
- CALIBER: 300 BLACKOUT SUPERSONIC AND SUBSONIC ONLY
- FULL AUTO RATED\*
- LENGTH: 6.7"
- DIAMETER: 1.5"
- WEIGHT: 14 OZ
- MATERIAL: TITANIUM
- TUBE FINISH: DESERT TAN CERAKOTE WITH REDUCED VISUAL-IR SIGNATURE
- CORE FINISH: TITANIUM
- MOUNT: 5/8-24 THREAD

\*Fully automatic fire is defined as 4-8 round bursts, every 3 to 6 seconds.



## INSTALLATION AND REMOVAL:



WARNING! DO NOT INSTALL OR REMOVE THE GMT-300 BLK WHILE THE FIREARM IS LOADED.

First remove the magazine from the firearm. Second, visually and manually check and clear the chamber and action. Make certain the firearm is unloaded at all times.

**INSTALLATION:** Remove any thread protector or muzzle device. Thread the suppressor clockwise onto the muzzle.

HAND TIGHTEN ONLY. DO NOT OVER TIGHTEN.

**REMOVAL:** Unscrew the suppressor by hand. If necessary use a 3/8 inch socket wrench inserted into the muzzle to loosen.

CAUTION! DO NOT REMOVE THE GMT-300 BLK WHILE THE SUPPRESSOR IS HOT.

